

Heat Pipe Condensing Economiser

By

Hussam Jouhara (*Brunel*)

Mark Boocock (*Econotherm*)



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Steam Generator, China National Offshore Oil Corp, China Sea, China



- GA 6400 smooth pipe 2 stage steam generator
- On-site assembly
- High reliability required for offshore location
- Low footprint required by space limitations
- Instant start up from gas turbine

Gas to Steam

Exhaust Temp In/Out	400 C/250 C
Water/Steam Temp In/Out	50 C/180 C
Exhaust Flow/Steam Rate	130,000/ 8,000 Kg/h
Energy Recovered	6.4 MW
Recovered Energy	£2,100K p/a
Project Cost	£1,200K
Payback Period	7 Months
£/KW recovered	£328



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Gas to Air Unit, Automotive, Aluminium Furnace, USA



Gas to Air

Exhaust Temp In/Out	400 C/266 C
Air Temp In/Out	30 C/293 C
Exhaust/Air Mass Flow	12,000/ 6,374 Kg/h
Energy Recovered	528 KW
Recovered Energy	\$155K p/a
Project Cost	\$150K
Payback Period	16 Months
\$/KW recovered	\$123 (£76)




- GA 360 smooth pipe heat exchanger
- 500 kW combustion air pre-heater
- High particulate matter exhaust from furnace
- Low fouling, easy cleaning and maintenance, high reliability
- Unit positioned outside main factory premises
- Customer advised it was not possible by consultants (acid etc)



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

3 Kiln Heat Recovery, RAK Ceramics, UAE



Gas to Air

Exhaust Temp In/Out	235 C/162 C
Air Temp In/Out	34 C/160 C
Exhaust/Air Mass Flow	41,771/ 27,400 Kg/h
Energy Recovered	970 KW
Recovered Energy	£209K p/a
Project Cost	£190K
Payback Period	11 Months
£/KW recovered	£195



- GA 970 smooth pipe heat exchanger
- 970 kW drier air pre-heater sourcing exhaust from 3 tunnel kilns
- Pre-heated air delivered to multiple usage points
- High particulate matter exhaust from kilns
- Integrated moving plate cleaning system



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.



Heat Pipe Condensing Economiser



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.





Heat Pipe Condensing Economiser in the Food Industry



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Site visit summary

- Location and date: ARLUY (Spain), June-2017
- Heat Source: Indirect radiant oven for biscuit cooking
- Heat sink: pre-heating water used for cleaning manufacturing machines




This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Proposed Application



- The proposed HPCE will be installed downstream the gas burner
- The HPCE will preheat the water before it enters the fuelled boiler
- Heat source (gas fire) is available 24/7





This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Space availability



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Space availability




This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

Heating Demand

Cleaning Water specifications

Temperature	10-18°C
Pressure	4bar
Flow rate	15 L/min
Pipe size	1"/2
Duty cycle	2 hrs continuously, 3 times/week (220hrs/year approx.)



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

HPCE Thermal design




Thermal Design Parameters	
Exhaust mass flow rate	357 kg/h
Water Mass flow Rate	500 kg/h
Exhaust average specific heat capacity	0.288 Kcal/Kg.°C
Water average specific heat capacity	1 Kcal/Kg.°C
Exhaust inlet temperature	203°C
Exhaust outlet temperature	50°C
Water Inlet temperature	20°C
Water Outlet temperature	45-48°C
Recovered heat	18.349 kW




This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

HPCE Mechanical Design




This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

HPCE Mechanical Design



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.


HPCE Installation



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.


HPCE Installation

Sensor Layout




This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

HPCE Installation



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.

HPCE Installation



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 680599.